



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

September 21, 2018

Kevin Kutcel  
Agent  
New Nautical Coatings Inc.  
14805 49<sup>th</sup> St  
Clearwater, FL 33762

Subject: Notification per PRN 98-10 – Minor Label Changes  
Product Name: Copper Free Waterborne Antifouling Coating  
EPA Registration Number: 44891-17  
Application Date: August 31, 2018  
Decision Number: 544283

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

The following alternate brand names have been added to the product record:

- Mission Bay CSF
- Sea Hawk Mission Bay CSF

If you have any questions, you may contact Joe Daniels at (703) 347-8669 or via email at [daniels.joseph@epa.gov](mailto:daniels.joseph@epa.gov).

Sincerely,

A handwritten signature in blue ink that reads "E. Miederhoff". The signature is written in a cursive style with a large, stylized initial "E".

Eric Miederhoff  
Product Manager 31  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

Notes to reviewer are bracketed [ ]  
Statements in parenthesis are optional or alternative text ( )  
~~Strike through~~ Delete  
( ) Add

**NOTIFICATION**

44891-17

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

09/21/2018

[Brand Names]  
COPPER FREE WATERBORNE ANTIFOULING COATING

[Alternative Brand Names]

~~(SEA HAWK MISSION BAY CSF COPPER-FREE ANTIFOULING COATING)~~

(Mission Bay CSF)

(Sea Hawk Mission Bay CSF)

KEEP OUT OF REACH OF CHILDREN

**DANGER**

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

ACTIVE INGREDIENT:

ACTIVE INGREDIENT: Zinc Omadine.... 4.02%

~~INERT~~ (OTHER) INGREDIENTS.....95.98%

TOTAL .....100.00%

**LIMITED WARRANTY:** The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.)

**[OPTIONAL MARKETING STATEMENTS:]**

Copper Free Technology

(Sea Hawk)

(Yacht Finishes)

(Premium Quality)

(Antifouling Coating)

(California Compliant)

(Tough on Barnacles)

(Hand Crafted in America!<sup>SM</sup>)

(Self Polishing)

(Antifouling Paint)

(Ablative)

(Hard Ablative)

(Antifouling Bottom Paint)

(Copper-Free)

(Copper-Free Antifouling Coating)

(Copper-Solvent-Free)

(Copper-Solvent-Free Antifouling Coating)

{California Compliant}

{CA VOC Code Compliant}

{Grams Liter}

{Hand Crafted in the USA}

{American Owned and Hand Crafted}

(Premium Yacht Finished)

(Antifouling Paint)  
(Multi-season Protection)  
(Water-Based Antifouling)  
(4505 Black)  
(4502 Bright Blue)  
(4503 Bright Green)  
(4510 Bright White)

[Optional Graphics]



**PREMIUM QUALITY**

**Mission Bay<sup>CSF</sup>**  
Copper-Free Antifouling Coating



[ABOVE BAR CODE WILL APPEAR ON EACH CAN AND THE NUMBERS PROVIDED THE ABOVE WILL CORRESPOND WITH THE BAR CODE ISSUED FOR THAT PRODUCT.]



[Above will be used with contents and manufacturer depending on the size]

[Net Contents:] (5-gallon pail 18.927 ), (Gallon 3.785 Liters), (Quart 0.9463 Liters)

(Batch Code) [to appear on front or back panel of the label or immediate container depending on the container type/size]

#### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

#### GENERAL DESCRIPTION

Hard abrasive, multi-seasonal, water-based antifoulant. Provides protection against algae, barnacles, annelids, tunicates, bryzoa, hydroids, zebra mussels and other fouling organisms. **Copper Free Waterborne Antifouling Coating White** is abrasion resistant for scrubbing, trailering and dry storage. Reduces paint buildup. This product may only be used to treat the surfaces of hulls on boats and vessels. This product is intended for both salt and fresh water use. Product applies easily and dries quickly. It may be used over old antifouling finishes in good condition. **Copper Free Waterborne Antifouling Coating White** (This) is an antifouling paint in a high-technology vehicle that withstands frequent trailering, beaching and launching. Shake vigorously for several minutes with a mechanical paint shaker before use. Due to the settlement in the product, if this product is not properly shaken it will become ineffective.

**SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION**

#### PRODUCT INFORMATION

Finish/Sheen:	Semi-Glos
Converter:	One Pack
Volume Solids:	44% ± 2%
Mix Ratio:	One Pack
Shipping Weight:	13-14 Lbs./Gal.
Flash Point:	N/A
Film Thickness:	5 mils wet equals 2.2 dry per coat
Recommended Coats:	3
Theoretical Coverage:	320 Sq. Ft./Gal. @ recommended film thickness

#### APPLICATION DETAILS

Sweat-In Time:	Not Applicable
Thinner:	N/A

Cleaner: Water

**Overcoating Interval    Drying Time (Hrs)**

Substrate Temp.	Touch	Min.	Max.	Launch
73°F (23°C)	2 Hrs	1 Hr	N/A	12 Hrs
95°F (35°C)	1 Hr	1 Hr	N/A	12 Hrs

**REGULATORY DATA**

**VOC:** 113 Grams/Liter

**LIMITATIONS:** Apply in good weather when air and surface temperature are above 50°F (10°C). Surface temperature must be at least 50°F (10°C) 5°F (1°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating application procedures. See published data sheets for more specific application data. As application, environment and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

**APPLICATION:** This product can be applied (Apply 3 coats by brush, roller or spray.)

**THINNING:** We do not recommend thinning.

**CLEANUP:** Clean all equipment immediately after use with water.

**STORAGE AND DISPOSAL**

Do not contaminate food, feed or water by storage or disposal.

**Storage:** Do not store near heat or open flame.

**Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** Non-refillable container. Do not reuse or refill this container. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities. (Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.)

**SAFETY:** Read and observe all precautionary statements on this label.

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**DANGER-CORROSIVE.** Causes irreversible eye damage. Harmful if swallowed or absorbed through the skin. May be fatal if inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Do not get in the eyes, on skin, or on clothing. Do not breathe vapor or spray mist. Wash thoroughly after handling with soap and water, and before eating, drinking or using tobacco. Remove contaminated clothing and wash clothing before reuse. When mixing and loading, or cleaning equipment, wear a chemical resistant apron.

~~Residential PPE: Residential (non-commercial) users are advised to~~ **(PPE: W)**ear chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long-sleeved shirt and long pants, socks, and shoes. While removing existing paint by sanding or blasting, or applying new paint by brush, or roller, (or spray,) ~~it is advised to~~ wear a (half face NIOSH approved respirator (TC-84A) with organic vapor cartridges and R or P combination filters; **OR** a full face NIOSH approved respirator (TC-84A) with organic vapor cartridges and any R or P combination filters; a NIOSH approved gas mask (TC-14G) with an Organic Vapor Cannister and HE Filter; **OR** a NIOSH approved powered air purifying respirator (TC-23C) with an organic vapor cartridge and HE filter.)  
respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHANIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHANIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 prefilter.

**Commercial PPE:** Users must wear a disposable coverall with hood, chemical resistant gloves, protective eyewear (goggles, safety glasses or face shield), long sleeve shirt and long pants, socks, and chemical resistant footwear. While removing existing paint by sanding or blasting, or applying new paint, user must wear a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHANIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHANIOSH approval number TC-14G), or a NIOSH approved full face respirator with an organic vapor removing cartridge with a P-100 prefilter.

### ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposing of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

### PHYSICAL AND CHEMICAL HAZARDS

Combustible. Do not use or store near heat or open flame.

FIRST AID	
<b>If in eyes</b>	• Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
<b>If swallowed</b>	• Call poison control center or doctor immediately for treatment advice. • Do not give any liquid to the person. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give anything by mouth to an unconscious person.
<b>If inhaled</b>	• Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
<b>If on skin or clothing</b>	• Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15 – 20 minutes. • Call a poison control center or doctor for treatment advice.
<b>(Have the product container or label with you when calling a poison control center, doctor or going for treatment.)</b>	
For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada <del>+1-703-527-3887</del> (+1-703-741-5970) CHEMTREC. Account #15570.	
For Non Emergencies call New Nautical Coatings Inc., Within the USA and Canada 1-800-528-0997, Outside USA and Canada +1-727-523-8053.	
<b>NOTE TO PHYSICIAN:</b> Probable mucosal damage may contraindicate the use of gastric lavage.	

**E.P.A. Registration No. 44891-17**

**E.P.A. Establishment No. 44891-FL-1**